



BOD Incubator

Technical Specification

Temperature Range: 10° C to 60 °C

Accuracy: ±0.2 °C

Uniformity: ±1.0 °C

Features

21 CFR PART-11 Compliance
Log data, Event data, Audit Trail data, E-Records & E-signatures, Graphical analysis & Data acquisition.

Optional Features

STAND BY REFRIGERATION SYSTEM
SCANNER
GSM TECHNOLOGY
HOOTER SYSTEM
EXTRA TRAY

Sizes:

Models	MK*-20BO	MK*-40BO	MK*-60BO	MK*-80BO	MK*-100BO	MK**-S100BO	MK**-S200BO	MK**-S300BO
Features	200 Ltrs	400 Ltrs	600 Ltrs	800 Ltrs	1000 Ltrs	1000 Ltrs	2000 Ltrs	3000 Ltrs

Interior Dimension

Width in mm	600	700	700	700	800	800	1750	2050
Depth in mm	400	600	800	800	800	800	800	850
Height in mm	850	950	1100	1450	1600	1600	1700	2000

Exterior Dimension

Width in mm	760	860	860	860	960	960	2090	2390
Depth in mm	865	1060	1265	1265	1265	1265	1310	1360
Height in mm	1450	1550	1700	2100	2250	2210	1890	2190

Trays

No of Trays	2	3	3	4	4	4	8	12
Type	Wiremesh Type							
Tray Spacing	Every ½" Adjustable						-	

Power Supply

Power Supply	Single Phase, 230V 50Hz							
Power Rating	1.5KW	2KW	2KW	3KW	3KW	3KW	4KW	4KW
Warranty	12 Months							

Other sizes also available as on requirement.

Models	Material of Construction	
	Interior	Exterior
MK1	S.S.304 Dull Finish	G.I. Powder Coated
MK2	S.S.304 Dull Finish	S.S.304 Dull Finish
MK3	S.S.316 Dull Finish	S.S.304 Dull Finish

NOTE:

MK* :- MK1 / MK2 / MK3

MK**-S :- Split type Condensing Unit

MK**- S200BO & MK**- S300BO are Panel & Trolley type (Split Type Condensing Unit)



For information log on: www.mackpharmatech.com